

# TYPE N MOUNTS



**J2.5 Scope with  
Type N Mount**

N Mounts (side bracket design) are pressed from tough alloy steel. They are similar to the former Type T Mounts but are wider, stronger and neater.

Four widely spaced attaching screws and rigid clamping of the scope tube assure rigidity. N Mount was designed to provide an inexpensive but reliable scope mount and has been proved under all conditions and on large caliber rifles.

The N Mount for each gun is shown in the list.

Make, Model of Rifle	Position of Scope	
	Low	High
ENFIELD (receiver rounded like Remington 30) . . . . .	N1	N4
H & R 65, 165, 365 . . . . .	N2	N3
KRAG (If central mounting interferes with ejection, offset scope to left) . . . . .	N2	N3
MARLIN high power lever actions . . . . .	N5	N5
39A round barrel (attach to barrel) . . . . .	N2	N3
39 octagon (attach to side of barrel) . . . . .		N5
A1, 50, 80*, 81 . . . . .	N2	N3
MAUSER* with straight receiver . . . . .	N1	N4
MONTGOMERY-WARD bolt actions and auto loaders, all models . . . . .	N2	N3
80 Slide action . . . . .	N5	N5
MOSSBERG bolt actions and auto loaders, all models . . . . .	N2	N3

Make, Model of Rifle	Position of Scope	
	Low	High
REMINGTON 30; 720 . . . . .	N1	N4
14, 141, 24, 241, 12, 121, 25 . . . . .	N5	N5
12C Octagon barrel (attach to barrel) . . . . .		N5
37 . . . . .		N3
510, 511, 512, 513, 521T, 550, 33*, 34*, 41*, 341* . . . . .	N2	N3
SAVAGE 4, 5, 6, 7, 19, 23, 33, 219, 40, 45 . . . . .	N2	N3
25, 29 . . . . .	N5	N5
20* . . . . .	N1	N4
SEARS-ROEBUCK, RANGER 101.20 101.23, 101.13, 101.16, 101.19, 101.22, 103-13, 103-4, 103-2*, 36* . . . . .	N2	N3
SPRINGFIELD GOVT.* .30/06 and .22 . . . . .	N1	N4
STEVENS 53, 56, 57, 66, 76, 762, 416, 417, 417½, 418, 418½, 26 . . . . .	N2	N3
27 (attach to side of barrel) . . . . .		N5
325 . . . . .	N1	N4
STEVENS-SPRINGFIELD 15, 84, 85, 86, 87, 872 . . . . .	N2	N3
WINCHESTER 54*, 70 . . . . .	N1	N4
61, 65, 67, 10 . . . . .	N5	N5
63, 03 (attach to barrel, J Scopes) . . . . .	N2	N3
63, 03 (attach to receiver, G Scopes) . . . . .		N5
90 (attach to right side of barrel) . . . . .		N5
06, 62, 62A (attach to right side of barrel; can be offset slightly to left to permit freer ejection) . . . . .		N3
52*, 60*, 67*, 68*, 57, 69, 72, 74, 75, 69A . . . . .	N2	N3

Rifles marked \* require altering of bolt handle if scope used in low position except with J Model when mounted forward.

**NOTE:** Model G Scopes (like other makes of low priced scopes) have short eye relief and for this reason should not be used on high power rifles. When using any of our scopes on rifles having any noticeable recoil, be certain that the scope is placed far enough forward on the gun to prevent contact of the scope and face or scope and spectacles, when the rifle recoils.